

MUXX ÖL

MUXX ÖL

MUXX ÖL

MUXX ÖL

MUXX ÖL

MUXX ÖL

**MUXX ÖL**

Deutschland Schmierstoffe

# **BRAKE FLUID DOT 4+**



German Quality

MUXX OIL GmbH  
15 Frankenhauser St., 12249 Berlin,  
Germany.  
Office: +49 (0)30 61633942  
Website: [www.muxxlube.de](http://www.muxxlube.de)  
E-Mail: [service@muxxlube.com](mailto:service@muxxlube.com)

## Description

- Brake fluid for hydraulic brake and clutch systems. Due to the low deep temperature viscosity this brake fluid is especially recommended for brake systems with ABS, TCS and ESP/DSC.
- Follow vehicle manufacturer's recommendations when adding brake fluid.
- Keep brake clean and dry. contamination with dirt, water, petroleum products or other materials may result in brake failure or costly repairs.
- Store brake fluid only in its original container. keep container clean and tightly closed to prevent absorption of moisture.

## Performance Levels

SAE J1704

FMVSS 116 DOT 4

ISO 4925

Test Item	Typical Spec.	Typical Result
Density @20°C	kg/l	Report
Kin. Viscosity @-40°C	cSt	1,700
Kin. Viscosity @100°C	cSt	2.69
Water by Weight	%	0.045
PH		7.5
ERBP		248
WET ERB		162
SBR Volume 120 deg C	mm	0.6
SBR Length 120 deg C	%	6.5

\*The Above Test Result is subject for change and for reference only



**EELQMS**  
EUROPEAN ENGINE  
LUBRICANTS QUALITY  
MANAGEMENT SYSTEM


[muxxlube.de](http://muxxlube.de)