



400 SP 10W40



German Quality

MUXX OIL GmbH
Hauptstr. 117, 10827 Berlin,
Deutschland.
Office: +49 (0)30 61633942
Website: www.muxxlube.de
E-Mail: service@muxxlube.com

Description

-C 400 SP 10W40 is a high performance fuel saving semi synthetic oil for gasoline- and diesel engines of passenger car and light vans with or without turbocharger. This product is NOT suitable for diesel engines with a Diesel Particle Filter (DPF).

-C 400 SP 10W40 is formulated with high quality refined mineral and synthetic base stocks in combination with a special additive technology to achieve the following performance:

- Very good low temperature properties.
- Protection to wear by cold start.
- Very high thermal- and oxidation stability.
- Excellent resistance against foaming, corrosion and wear.
- High dispersancy and detergency level.
- High viscosity index.

Performance Levels

API SP

| Test Item | Typical Spec. | Typical Result |
|-----------------------|--------------------|----------------|
| SAE Grade | | 10W40 |
| Density @15°C | kg/m ³ | 859 |
| Kin. Viscosity @40°C | mm ² /s | 96.06 |
| Kin. Viscosity @100°C | mm ² /s | 14.51 |
| Viscosity Index | | 155 |
| Flash Point COC | °C | 233 |
| Pour Point | °C | -37 |
| Total Base Number | mgKOH/g | 7.7 |
| Color | | L2.5 |



EELQMS
EUROPEAN ENGINE
LUBRICANTS QUALITY
MANAGEMENT SYSTEM



*The Above Test Result is subject for change and for reference only

