

MUXX ÖL

MUXX ÖL

MUXX ÖL

MUXX ÖL

MUXX ÖL

MU

MUXX ÖL

Deutschland Schmierstoffe



H 200 CF-4 15W40



German Quality

MUXX OIL GmbH
15 Frankenhauser St., 12249 Berlin,
Germany.
Office: +49 (0)30 61633942
Website: www.muxxlube.de
E-Mail: service@muxxlube.com

Description

- H 200 CF-4 15W40 is mixed fleet diesel engine oil incorporating high quality minerals oils and performance additives, suitable for use in a wide variety of diesel engine designs, including turbocharged versions.
- This grade will protect engine components from rust and corrosion and provide high levels of engine cleanliness, H 200 CF-4 15W40 is an economical choice for company servicing light and heavy commercials engines.
- H 200 CF-4 15W40 can be used in a range of vehicle and engine types, including commercial vehicles, buses, coaches, cars and vans. H 200 CF-4 15W40 may also be used in hydraulic systems where a product of this type and specification is required.

Performance Levels

API CF-4

Test Item	Typical Spec.	Typical Result
Density @15°C	kg/m ³	868
Kinematic Viscosity at 100°C	mm ² /s	15.11
Kinematic Viscosity at 40 °C	mm ² /s	119.17
Viscosity Index		132
Flash Point (Open)	°C	234
TBN, mg/KOH/g	mgKOH/g	10.5
Pour Point	°C	-26
Color		2.5
CCS -20°C	cP	5900

*The Above Test Result is subject for change and for reference only


muxxlube.de