



600 10W40



German Quality

MUXX OIL GmbH
15 Frankenhauser St., 12249 Berlin,
Germany.
Office: +49 (0)30 61633942
Website: www.muxxlube.de
E-Mail: service@muxxlube.com

Description

X 600 10W40 is an universal high performance fuel saving semi synthetic oil for use in gasoline and diesel engines of passenger car and light vans with or without turbocharger. This product is unsuitable for diesel engines equipped with a Diesel Particle Filter (DPF).

X 600 10W40 is formulated with high quality refined mineral and synthetic base stocks in combination with a special additive technology to achieve the following performance:

- Very good low temperature properties.
- Protection to wear by cold start.
- Very high thermal- and oxidation stability.
- Excellent resistance against foaming, corrosion and wear.
- High dispersancy and detergency level.
- High viscosity index.

Performance Levels

API SN

ACEA A3/B3

MB 229.1

VW 501.01/505.00

Test Item	Typical Spec.	Typical Result
SAE Grade		10W40
Density @15°C	kg/m ³	868
Kin. Viscosity @40°C	mm ² /s	96
Kin. Viscosity @100°C	mm ² /s	14.2
Viscosity Index		150
Viscosity CCS @-30°, max.	cP	7000
Flash Point COC	°C	201
Pour Point	°C	-39
Total Base Number	mgKOH/g	8.0
Sulphated Ash	%Wt	0.95

*The Above Test Result is subject for change and for reference only



EELQMS

EUROPEAN ENGINE
LUBRICANTS QUALITY
MANAGEMENT SYSTEM

