

MUXX ÖL

MUXX ÖL

MUXX ÖL

MUXX ÖL

MUXX ÖL

MU

MUXX ÖL

Deutschland Schmierstoffe



600 SP 0W20



German Quality

MUXX OIL GmbH
Hauptstr. 117, 10827 Berlin,
Deutschland.
Office: +49 (0)30 61633942
Website: www.muxxlube.de
E-Mail: service@muxxlube.com

Description

-X 600 SP 0W20 is fully synthetic low viscosity multi-grade engine oil specially formulated to meet the cross age develop engines which emphasis on fuel efficiency requirements. Enhanced oil flow and film strength give essential protection during start up.

-X 600 SP 0W20 also employ the low ash additive technology which meet the requirement of the GPF system as well as the LSPI engines.

Performance Levels

API SP-RC ILSAC GF-6A GM dexos1™ Gen2

Test Item	Typical Spec.	Typical Result
SAE Grade		0W20
Density @15°C	kg/m3	842
Kin. Viscosity @40°C	mm2/s	47.19
Kin. Viscosity @100°C	mm2/s	8.72
Viscosity Index		166
Viscosity CCS @-35°, max.	cP	5810
X-rays	ppm	P-845 S-2416 Ca-1055 Zn-887
Noack	%	13
Total Base Number	mgKOH/g	7.3
HTHS 150°C, cP		2.6
Color		2.5

*The Above Test Result is subject for change and for reference only



EELQMS
EUROPEAN ENGINE
LUBRICANTS QUALITY
MANAGEMENT SYSTEM


muxxlube.de